

**OREGON CORNER RESTORATION FORM**

COUNTY: Umatilla DATE: 08/13/13

CORNER DESIGNATION: 3N32, V15, The North One-Quarter Corner of Section 34.

PREVIOUS RENEWALS/SURVEYS ETC.: Corner originally established by David Chaplin, under Contract 107, dated September 1864, notes state: Set post for 1/4 Sec. cor. in mound of Earth with charred stake pits & c as per instructions. Corner position computed by single proportion measure by Stephen Haddock on Survey 06-606-C, record states: "Corner point calculated following the 1973 BLM manual of instructions, nothing set or found."

MONUMENT AND ACCESSORIES FOUND: None.

MONUMENT MARKING DETAIL:

T3N R32E  
1 S27  
4 S34  
2013  
PLS 54657

MONUMENT SET: Corner position reestablished by single proportion measurement between the Northeast and Northwest corners of Section 34. At the reestablished corner point, set 2 3/8" brass cap on a 1 1/4" x 30" galvanized iron pipe with top 20" below ground in farmed field, marked as shown in "Monument Marking Detail", from which:

- A silver deep-1 magnet buried 20" in the ground bears North 48° East, 46.1 feet.
  - A pink deep-1 magnet buried 20" in the ground bears South 41 1/2° East, 33.9 feet.
  - A blue deep-1 magnet buried 20" in the ground bears South 51 1/2° West, 32.2 feet.
  - An orange deep-1 magnet buried 20" in the ground bears North 47° West, 33.4 feet.
- Buried bearing object tags with magnets.

LOCATION AND COMMENTS: Falls in a farmed field with no features.

OREGON STATE PLANE COORDINATE, North Zone, NAD 83(91), International Feet:

Monument: N= 747155.07' Cor. position on latitudinal arc: N=747154.90  
E= 8637118.88' E=8637118.88

FIRM: Wells Surveying  
P.O. Box 1696  
Pendleton, OR 97801

COMPASS DECLINATION: 18° East Surveyor's Seal

Witnesses: Jason Wells, PLS  
Dean Roy

\3N32V15

