


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:



A BASALT STONE 18"x15"x10" IN A MOUND OF STONES

15" PINE N84E 36 LKS.
30" PINE N62W 55 LKS.

Description of corner evidence found:

36" PINE N62W 36.3' SCRIBING VISIBLE

Description of monument and accessories established to perpetuate the original location of this corner:

SET A 2"x30" IRON PIPE WITH A BRASS-CAP MARKED:

T6S R30E
S11 S12
S14 S13
1978
PLS 346

10" FIR S38W 39.6' MARKED: T6S R30E S14 BT
22" FIR N74E 53.9' MARKED: T6S R30E S12 BT
16" FIR S66E 64.1' MARKED: T6S R30E S12 BT

ALL BT'S HAVE A RED-PAINTED STRIPE, BEARING TREE SIGN, AND AN ATTENTION SIGN. THE NEW BT'S HAVE A BRASS WASHER STAMPED PLS 346 NAILED TO THE LOWER FACE. THERE IS A FENCE POST ON LINE NEAR THE CORNER.



Office of... COUNTY SURVEYOR... County of... UMATILLA...
State of... OREGON... I hereby certify that the within instrument was filed in this office
for record on the... day of... 19...
W. O. Harris by...
(COUNTY OFFICIAL) (DEPUTY)

RECEIVED SEP 11

1978

(S-2)